



Eco-Friendly



Non-Toxic

# ACRYLIC EMULSION

# SINOGRACE

The Chemical Company

## Architectural Coatings

### WF-600 JS Cement Waterproof Emulsion

#### DESCRIPTION

WF-600 Cement-based waterproof coating is a styrene and acrylic polymer polymerization produced by the waterproof material.

#### TYPE

Styrene acrylic copolymer emulsion

#### KEY FEATURES

- Film forming high hardness
- Self - crosslinking acrylic copolymer emulsion
- Good compatibility with cement and easy construction
- Excellent low temperature flexibility, excellent extensibility and Tensile strength v paint, the film high gloss, good resistance to cracking

#### TYPICAL PROPERTIES

<b>Appearance</b>	Milky white liquid
<b>PH</b>	5.0-7.0
<b>Solid content</b>	55%
<b>Glass Transition Temperature</b>	0°C
<b>Viscosity (25°C)</b>	500-3000cP
<b>Ionic</b>	Anion
<b>Tensile strength</b>	>1.1 MPa
<b>MFFT</b>	10°C
<b>Freeze-Thaw Resistance, 5 cycles</b>	Pass

#### APPLICATION

- Basecoats
- Roof coverings
- Anticorrosion protection
- High-flexibility tile adhesives
- Additive for hydraulic binder systems
- Rigid and flexible waterproofing slurries for sealing in conjunction with tiles and protective surface coatings

#### STORAGE AND HANDLING

- Available in 200 kg/ barrel or 1000kg/barrel (IBC)
- Store products in tightly closed original containers at 5-35°C
- Shelf life: 6-9 months from delivery date
- According to non-dangerous goods transport

Anhui Sinograce Chemical Co., Ltd.

Tel: +86-0551-63459511

Email: sales@sinogracechem.com

Add.: Hefei city, Anhui province, China

Mob: +86 15755193346