



The Chemical Company

Adhesive/Binder

PU-302 Modified water based polyurethane glass coating

DESCRIPTION	It is special water based polyurethane modified by epoxy resin. Good compatibility with pigment and other additives. It is can be formulated as transparent, frost finishes or other colors. It forms a hard, durable, colorful coating.	
ТҮРЕ	Modified aliphatic polyurethane-epoxy resin	
	• Formaldehyde free	
KEY	• Anti-UV and excellent water resistant	
	• Excellent adhesive force and h	neat resistance
FEATURES	• High hardness and good abrasion resistant	
	• Excellent weatherability and s	alt-fog resistance
	Appearance	Milky white liquid
	рН	7.0-9.0
TYPICAL PROPERTIES	Solid content	40±1%
	Charge	Anionic
	Viscosity (25°C)	300-800cP
	Hardness	>4H
	Dry time for Touch (25°C)	1-2 hours
	Dry time for Test (25°C)	24 hours
	• Glass varnish	

- **APPLICATION** Glass bottles
 - Artistic glassware

STORAGE	• Available in 200 kg/ barrel or 25 kg/ barrel
AND	 Store products in tightly closed original containers at 5-40°C Shelf life: 9 months from delivery date
HANDLING	• According to non-dangerous goods transport