



## **Water-based Acrylic Emulsion**

## SA-209 Styrene acrylic emulsion for exterior wall primer paint

DESCRIPTION	SA-209 is an exterior wall primer paint with excellent water resistance and adhesion	
TYPE	Styrene acrylic copolymer emulsion	
KEY FEATURES	<ul> <li>Excellent water resistance, alkali resistance and salt fog resistance</li> <li>Excellent adhesion to substrate and finish coating</li> <li>Low VOC, APEO free</li> </ul>	
TYPICAL PROPERTIES	Appearance	Milky white emulsion with light blue shade
	pH	7-9
	Solid content	48±1%
	Ionicity	Anionic
	Viscosity(25℃	3000-8000cPs
	)	
	MFFT	20℃
	Ionic diameter	0.1-0.2μm
	TG	21℃
APPLICATION	• Primer paint	
• 200kg/Plastic Barrel		Barrel
STORAGE	• Store products in tightly closed original containers at	
AND	5-35°C, avoid freezing and high temperature,	
HANDLING	• Shelf life: 6 months from delivery date	
		non-dangerous goods transport

Anhui Sinograce Chemical Co., Ltd. Tel: +86-0551-63459511

Email: sales@sinogracechem.com

Add.: Hefei city, Anhui province, China

Mob: +86 15755193346