



Eco-Friendly

ACRYLIC EMULSION



Non-Toxic

SINOGRACE

The Chemical Company

Architectural Coatings

SA-206 Styrene Acrylic Emulsion

DESCRIPTION

Acrylic Emulsion is a small particle size, acrylic polymer latex that lends itself to a broad spectrum of paint formulations, resulting in coatings with excellent long-term durability. It has excellent calcium ion stability, dilution stability, mechanical stability and freeze-thawing stability.

TYPE

Styrene acrylic copolymer dispersion

KEY FEATURES

- High pigments & fillers loading capability
- Strong adhesive ability, good color performance
- Good resistance to weather, water, alkali, staining & scrubbing
- Excellent calcium ion stability, dilution stability, mechanical stability and freeze-thawing stability

TYPICAL PROPERTIES

Appearance	Milky white liquid
pH	7-9
Solid content	55±1%
Glass Transition Temperature	20℃
Viscosity (25℃)	500-1800cP
Ca²⁺ stability 5%CaCl₂: emulsion =1:3, 48h, No Flocculation, No Stratification.	Pass

APPLICATION

- Exterior and interior wall coatings

STORAGE AND HANDLING

- Available in 200 kg/ barrel or 25 kg/ barrel
- Store products in tightly closed original containers at 5-40℃
- Shelf life: 9 months from delivery date
- According to non-dangerous goods transport

Anhui Sinograce Chemical Co., Ltd.
Tel: +86-0551-63459511
Email: sales@sinogracechem.com

Add.: Hefei city, Anhui province, China
Mob: +86 15755193346