



Ink Binder

BA-8204 Water-based acrylic emulsion

DESCRIPTION	BA-8204 is a non-film forming acrylic polymer emulsion. It has good compatibility with ethanol, isopropanol and other solvents. It is especially suitable for the production of flexo and gravure printing inks.	
ТҮРЕ	Acrylic Polymer Dispersion	
KEY FEATURES	 Fast drying Resistance to bond Good color development, high gloss, Excellent adhesion and scrub resistance Excellent transferability and printability 	
	Appearance	Semi-translucent liquid
TYPICAL	рН	7.0-9.0
	Solid content	48±1%
	Viscosity (25°C)	500-1000cP
PROPERTIES	MFFT	100℃
	Particle diameter	$0.1 \sim 0.2 \mu m$
APPLICATION	 Overprint varnish Water-based paper ink Corrugated paper or cardboard ink Water-based flexo and gravure ink 	
STORAGE	• Available in 200 kg/ barrel or 1000kg/barrel (IBC)	
	 Available in 200 kg/ barlet of 1000kg/barlet (iBC) Store products in tightly closed original containers at 5-35 °C 	
AND	 Store products in rightly closed original containers at 5-55 C Shelf life: 6-9 months from delivery date 	
HANDLING	 According to non-dangerous goods transport 	